



model 9400

AXION® steam water heater

OPERATION

When an emergency shower or eyewash is activated, the flow of water opens a steam control valve. The steam enters a brazed plate heat exchanger, instantly heating the water. A mixing valve blends hot and cold water to produce an output of 80° F (27° C) tepid water. Additional valves keep the system preheated, freeze protected and scald protected. The steam valve will remain closed should there be a loss of water pressure.

FEATURES & BENEFITS

FLOW RATES

Provides 3 to 25 GPM (11 to 95 LPM) of tepid water.

OPERATION

Operates on typical plant steam pressure, 45 - 60 PSIG (3 - 4 BAR) is recommended. Steam and water never mix, separated by brazed plate heat exchanger. Low pressure system is available for 15 - 30 PSIG (1-2 BAR) steam.

ASSE 1071 COMPLAINT THERMOSTATIC MIXING VALVE

Unit employs a paraffin-filled thermostatic mixing element that controls the valve spool to blend exactly the correct proportions of hot and cold water to achieve the target set-point. The valve spool is treated with a special non-stick coating that minimizes buildup of minerals and particulates that can cause valve sticking. The mixing valve design allows accurate control of flow from full shower flow to the low eyewash flow ratings shown.

INSTALLATION

Ease of installation, uses existing plant saturated steam and potable water supply. Union connections are provided for quick installation. Compact, lightweight design, easily supported by pipe connections.

SERVICING

Durable, protective enclosure can be readily removed for servicing.

MEDICALLY SUPERIOR RESPONSE®

AXION's superior design and technology provide a complete safety solution for increased victim comfort.



SPECIFICATIONS


Model 9400 - Steam Water Heater


	MAXIMUM		MINIMUM	
Outlet Flow Rate	25 GPM	95 LPM	3 GPM	11 LPM
Ambient Operating Temperature	120°F	49°C	-30°F	-34°C
Inlet Water Pressure	90 PSIG	6 BAR	55 PSIG	4 BAR
Inlet Water Temperature	80°F	27°C	40°F	4°C
Inlet Saturated Steam Pressure	60 PSIG	4 BAR	45 PSIG	3 BAR
Saturated Steam Temperature	350°F	177°C		
Cold Water Bypass Flow Rate	24 GPM @ 25 PSI Pressure Drop			
Water Inlet & Outlet Pipe Size	1 1/4" NPT (F)			
Steam Supply & Condensate Pipe Size	1" NPT (F)			
Steam Consumption	600 lb/hr @ 25 GPM Flow Rate, 20 lb/hr @ Idle			
Condensate Discharge Rate	12 GPH maximum			
Pressure Drop Water Inlet	25 PSI @ 25 GPM			

THIS DOCUMENT IS TRUE AND CORRECT AT TIME OF PUBLICATION. CONTINUED PRODUCT IMPROVEMENTS MAKE SPECIFICATIONS AND MEASUREMENTS SUBJECT TO CHANGE WITHOUT NOTICE.

NOTES:

1. DIMENSIONAL TOLERANCES: $\pm 1/2"$
2. RECOMMENDED WATER PRESSURE:
55 psi (3.79 bar) MIN.
90 psi (6.21 bar) MAX.
3. RECOMMENDED STEAM PRESSURE:
45 psi to 80 psi (3.10 bar to 4.14 bar)
MAXIMUM STEAM TEMPERATURE:
350° F (177° C).



**Haws®**

1455 McEPPELANE
SPARKS, NEVADA 89431
(775) 358-4712 FAX (775) 358-7424
E-MAIL: HAWS@HAWS.CO.COM
WEBSITE: WWW.HAWS.CO.COM

ECN: 4890
REVISED PER: FV
DATE: 07/02/18
SCALE: NA
DRAWING TYPE: INSTALLATION
SIZE: A
SHEET: 1 OF 1

MODEL(S)
9400
AXION STEAM WATER HEATER

REVISION
8

PART NUMBER
0002080243.D