

FEATURES & BENEFITS

FLOW SWITCH

The alarm is activated by an 1-1/4" IPS double pole, double throw brass flow switch that is supplied with an extra set of electrical contacts for remote alarm hook-up.

OPTIONS

For more information, visit www.hawesco.com or call (888) 640-4297.



SPECIFICATIONS

Model 9001EXP Class 1, Division 2, Groups B, C and D emergency alarm and light system features a red flashing light and 90 db at 10 feet (304.8 cm), buzzer that is operated by a double pole, double throw flow switch. Unit is activated when the emergency shower or eyewash is in operation. Switch will activate at 2.4 gpm (9.08 L). System can be mounted to pipe or wall with optional wall bracket that is provided. It is recommended to install unit where a shower or eyewash is in a remote or noisy location where user is unable to summon help. This alarm contains a multiple sets of contacts for remote activation alarm sites. Model is CSA electrical certified, TYPE 4. (Nema 4 equivalent). Tempering code T2C Voltage: 120 VAC, 50 or 60 cycles. Supply: 1-1/4" IPS.

APPLICATIONS

Specifically, this alarm can be used with almost any Haws eye or eye/face wash model. Model 9001EXP is CSA electrical certified, TYPE 4. (Nema 4 equivalent)